

STREETDECK BEV | ELECTROLINER



Accessibility

- 1 or 2 door option available
- Wheelchair compliant via electronic or manual ramp

Axle

- Front axle ZF RL 82 EC
- Rear axle ZF AV 133

Battery System

- 60Ah VDA PHEV2 modules (3P4S)
- CATL 442kWh & CATL 528kWh.

Battery Charging Systems

- CCS2.0 compliant Combo 2 Socket
- Up to 150kW plug-in charge rate available
- Up to 300kW opportunity charging available.

Battery Charging Times

- 442kWh: 2h 58m @ 150kW Charge Rate
- 528kWh: 3h 24m @ 150kW Charge Rate

Dimensions (MM / 10.6 / 10.99)

- Height: 4,395
- Length: 10,582
- Overhang front: 2,607
- Overhang rear: 2,495
- Wheelbase: 5,480
- Width: 2,520

Electric Traction

- Voith VEDS MD 250kW
- Torque 2,850Nm
- Max speed 2,850rpm

Gross Vehicle Weight

- 19,500kg

Legislative compliance

- Certified to NSSTA requirements

Optional Specification Items

Wright are able to offer a range of specification items that include but not limited to:

- Additional battery capacity
- Alloy wheels
- Camera mirror systems
- CCTV
- Destination Equipment & Next Stop Announcement Systems
- Drivers cab air conditioning
- Fire suppression systems
- Range of extended warranties
- Range of seating models available which include seat belts for both driver and passengers
- Telematics
- Wi-Fi

Passenger Capacity	442kWh	528kWh
- Maximum capacity:	96	86
- Max seated capacity:	74	72
- Max standing capacity	: 28	22

Vehicle Range

- 442kWh approx TBA miles: Electroliner SR
- 528kWh approx TBA miles: Electroliner ER

Vehicle Energy Consumption

- 454kWh at 0.68kWh/km (pending)
- 567kWh at 0.67kWh/km (pending)

Wheels & Tyres

- 275 / 70R x 22.5 Tubeless Tyre
- Choice of Bridgestone or Michelin







